

Advisory Circular [AC/AD – 008]

Guidance Material for Conducting an assessment of Tribhuvan International Airport to identify whether non-aeronautical ground lights or Laser Emitter near the aerodrome which may endanger the aircraft are properly shielded

FIRST EDITION March 2013

CIVIL AVIATION AUTHORITY OF NEPAL

LIST OF EFFECTIVE PAGES

	Chapter	Pages	Version/R evision	Date of Issue
List of effective pages		ii	0.00	March 2013
Reco	rd of amendments	iii	0.00	March 2013
Revis	ion History	iv	0.00	March 2013
Table	of contents	V	0.00	March 2013
Foreword		vi	0.00	March 2013
1.	Purpose	1	0.00	March 2013
2.	References	1	0.00	March 2013
3.	Application	1	0.00	March 2013
4.	Glossary	1	0.00	March 2013
5.	General	2	0.00	March 2013
6.	Laser-Beam Free Flight Zone	6	0.00	March 2013
7.	Laser-Beam Critical Flight Zone	6	0.00	March 2013
8.	Laser-Beam Sensitive Flight Zone	6	0.00	March 2013
9.	Normal Flight Zone	6	0.00	March 2013
10.	Lasers	6	0.00	March 2013
11.	Corrective Action	7	0.00	March 2013

March 2013 Rev. 0.00 Page ii

RECORD OF AMENDMENTS

Version/R evision Number	Chapter Changed	Pages Replaced	Signature	Date

March 2013 Rev. 0.00 Page iii

(Guidance Materials on shielding non-aeronautical Ground light or Laser Emitter at TIA AC/AD-008)

REVISION HISTORY

Edition	Date	Chapter/S ection	Details
001	March 2013	All	Advisory Circular: Guidance Materials on shielding non-aeronautical Ground light or Laser Emitter at TIA

March 2013 Rev. 0.00 Page iv

(Guidance Materials on shielding non-aeronautical Ground light or Laser Emitter at TIA AC/AD-008)

Table of Contents

		Page No.
Table of Contents		
Foreword		
1.	Purpose	1
2.	References	1
3.	Application	1
4.	Glossary	1
5.	General	2
6.	Laser-Beam Free Flight Zone	6
7.	Laser-Beam Critical Flight Zone	6
8.	Laser-Beam Sensitive Flight	6
9.	Normal Flight Zone	6
10.	Lasers	6
11.	Corrective Action	7

March 2013 Rev. 0.00 Page v

FOREWORD

Nepal as a Contracting State to the Convention on International Civil Aviation has an obligation to the international community to ensure that civil aviation activities under its jurisdiction are carried out in strict compliance with the Standards and Recommended Practices contained in the eighteen Annexes to the Convention on International Civil Aviation in order to maintain the required aviation standards.

As per the Civil Aviation Requirement for Aerodrome, CAR-14 Part 1, Aerodrome Design and Operations, First Edition -2012 an aerodrome operator requires to have a non-aeronautical ground light near an aerodrome which might endanger the safety of aircraft to be extinguished, screened or otherwise modified so as to eliminate the source of danger.

This Advisory Circular provides guidance to aerodrome operator (TIA) to monitor and properly shield a non-aeronautical ground light or Laser emitter near the aerodrome which may endanger the safety of aircraft.

Users of this Advisory Circular are reminded that the provisions of the Civil Aviation Authority Act 1996 (2053), CAAN Airport Certificate Regulations 2004 (2061) and other applicable regulatory documentation, rather than this Advisory Circular, determine the requirements of, and the obligations imposed by or under, the civil aviation legislation. Users should refer to the applicable provisions when any doubt arises.

This Authority may, without any prior notice, change the content of this Advisory Circular as appropriate.

Director General

Civil Aviation Authority of Nepal

Babar Mahal, Kathmandu, Nepal

March 2013

March 2013 Rev. 0.00 Page vi

1. PURPOSE

The purpose of this document is to provide guidance to conduct an assessment of Tribhuvan International Airport (TIA) to identify whether non-aeronautical ground lights or a laser emitter near the aerodrome, which may endanger the safety of aircraft, are properly shielded. Consequently, the aim of this Guidance Material is to properly assess the impact of any such activity and take appropriate measures to extinguish, shield or otherwise modify the hazardous non-aeronautical lights or LASER emitter near TIA which may strike pilot of an aircraft thereby endangering the safety of aircraft. This Guidance Material also provides general information and advice on measure to protect pilots of an aircraft from accidental laser beam strikes, on or in the vicinity of an aerodrome.

2. REFERENCES

- 2.1 Civil Aviation Authority of Nepal Act, 2053(1996)
- 2.2 CAAN Civil Aviation Regulation, 2058 (2002)
- 2.3 Civil Aviation Requirements (Aerodrome), CAR-14, 2012
- 2.4 ICAO Annex 14 Volume 1
- 2.5 ICAO Annex 11
- 2.6 ICAO Doc 9815

3. APPLICATION

The provisions under this guidance shall apply to Tribhuvan International Airport. TIA shall follow the mechanism and take appropriate measures to implement the relevant CAR -14, 2012 to ensure air safety.

4. GLOSSARY

- 4.1 **Irradiance** (**E**). Te power per unit area expressed in watts per square centimeter (W/cm²). Small value may be expressed as micro watts per square centimeter (μWcm²) or nano watts per square centimeter (nW/cm²).
- 4.2 **Laser.** 1). An acronym for light amplification by stimulated emission of radiation.
 - 2). A device that produce an intense, coherent, directional beam of optical radiation by stimulating emission of photons by electronic or molecular transition to lower energy level.

March 2013 Rev. 0.00 Page vii

- 4.3. **Maximum Permissible Exposure (MPE).** The internationally accepted maximum level of laser radiation to which human beings may be exposed without risk of biological damage to the eye or skin.
- 4.4 **Protected Flight Zones.** Airspace specifically designated to mitigate the hazardous effects of laser radiation.
 - (a) **Laser-beam critical flight zone (LCFZ).** Airspace in the proximity of an aerodrome but beyond the laser-beam free flight zone (LFFZ) where the irradiance is restricted to a level unlikely to cause glare effects.
 - (b) **Laser-beam free flight zone** (**LFFZ**). Airspace in the immediate proximity to the aerodrome where the irradiance is restricted to a level unlikely to cause any visual disruption.
 - (c) Laser-beam sensitive flight zone (LSFZ). Airspace outside, and not necessarily contiguous with, the LFFZ and LCFZ where the irradiance is restricted to a level unlikely to cause flash-blindness or after-image effects.
 - (d) **Normal flight zone (NFZ).** Airspace not defined as LFFZ, LCFZ or LSFZ but which must be protected from laser radiation capable of causing biological damage to the eye.

5. GENERAL

- 5.1 Lasers can produce a beam of light of such intensity that permanent damage to human tissue, in particular the retina of the eye, can be caused instantaneously, even at distances of over 10 km. At lower intensities, laser beams can seriously affect visual performance without causing physical damage to the eyes.
- 5.2 Protection of pilots against accidental laser beam strike has become a serious factor in aviation safety with the advent of the laser light display for entertainment or commercial purposes.
- 5.3 To protect the safety of aircraft against the hazardous effects of laser emitters, the following protected zones should be established around aerodromes:
 - (a) a laser-beam free flight zone (LFFZ),
 - (b) a laser-beam critical flight zone (LCFZ), and
 - (c) a laser-beam sensitive flight zone (LSFZ).
- 5.4 Figures 1, 2, and 3 may be used to determine the exposure levels and distances that adequately protect flight operations.
- 5.5 The restrictions on the use of laser beams in the three protected flight zones, LFFZ, LCFZ, and LSFZ, refer to visible laser beams only.

March 2013 Rev. 0.00 Page viii




Figure 1. Protected flight zones




Figure 2. Multiple runway laser-beam free flight zone

March 2013 Rev. 0.00 Page ix




Figure 3. Protected flight zones with indication of maximum irradiance levels for visible laser beams

- 5.6 Laser emitters operated by authorities in a manner compatible with flight safety are excluded from these restrictions. Typical examples of lasers used to support aviation include some cloud base or visibility measurement equipment, some bird harassing devices, and some aircraft docking guidance systems. Aerodrome authorities are to ensure that these lasers have the beam aimed in such a direction, and/or that the times of operation are controlled, to ensure no hazard is posed to aircraft operations.
- 5.7 In all navigable air space, the irradiance level of any laser beam, visible or invisible, is expected to be less than or equal to the maximum permissible exposure (MPE) unless such emission has been notified to the authority and permission obtained.
- 5.8 The protected flight zones are established in order to mitigate the risk of operating laser emitters in the vicinity of aerodromes.
- 5.9 The dimensions indicated for the various zones are given as guidance, but ICAO Doc 9815 advises that they have been found to provide for the safe operation of aircraft in the vicinity of aerodromes.

March 2013 Rev. 0.00 Page x

6. LASER-BEAM FREE FLIGHT ZONE

6.1 Within this zone, the intensity of laser light should be restricted to a level that is unlikely to cause any visual disruption. The irradiance should not exceed 50 nW/cm² unless some form of mitigation is applied. The level of brightness thus produced is indistinguishable from background ambient light.

7. LASER-BEAM CRITICAL FLIGHT ZONE

- 7.1 While the suggested extent of this zone is shown in the Figures, this zone may have to be adjusted to meet air traffic requirements.
- 7.2 Within this zone the irradiance should not exceed 5 μ W/cm² unless some form of mitigation is applied. Although capable of causing glare effects, this irradiance will not produce a level of brightness sufficient to cause flash-blindness or after-image effects.

8. LASER-BEAM SENSITIVE FLIGHT ZONE

- 8.1 The extent of this zone should be determined by the operations at the particular aerodrome. The LSFZ need not necessarily be contiguous with the other flight zones.
- 8.2 Within this zone the irradiance should not exceed 100 μW/cm₂ unless some form of mitigation is applied. The level of brightness thus produced may begin to produce flash-blindness or after-image effects of short duration; however, this limit will provide protection from serious effects.

9. NORMAL FLIGHT ZONE

- 9.1 The NFZ is any navigable airspace not defined as LFFZ, LCFZ or LSFZ. The NFZ should be protected from laser radiation capable of causing biological damage to the eye.
- 9.2 The maximum irradiance level (MIL), should be equal to or less than the maximum permissible exposure (MPE).

10. LASERS

10.1 Lasers used in the vicinity of aerodromes add to the known aviation-related problems associated with high intensity lights and can have a physiological impact upon pilots which could threaten aircraft safety, particularly at critical stages of flight such as final approach. Such physiological effects can include: glare, temporary flash blindness, after-image, and, possibly, eye injury. In addition, there is the potential for laser activity to dazzle and distract pilots of aircraft, and any planned laser activity must be organized to avoid this eventuality.

March 2013 Rev. 0.00 Page xi

10.2 Protection of the pilot against deliberate or accidental laser beam strikes has increased the risk of accidental illumination of aircraft from such displays, and therefore it is increasingly important to manage and mitigate those risks.

11. CORRECTIVE ACTION

11.1 Action by Aerodrome operator (TIA)

- 11.1.1 Include 'Non-aeronautical ground lights or LASER Emitter near the aerodrome' in the 'Daily Checklist of Airport Lighting Condition Report' form, and amend the Aerodrome Manual accordingly.
- 11.1.2 During daily inspection of the aeronautical ground lights, the personnel shall also observe whether there is any non-aeronautical ground light or a LASER emitter near the aerodrome, which may endanger the safety of aircraft, and make entry in the Reports.
- 11.1.3 Whenever any Pilot reports to Air Traffic Controller about such hazardous light(s), Air Traffic Controller shall raise a report to Director Flight Operation Department.
- 11.1.4 On getting such report(s), Aerodrome Operator shall take actions to extinguish, shield or otherwise modify the hazardous lights.
- 11.1.5 If required, Aerodrome Operator will take help of local administration.
- 11.1.6 If the Aerodrome operator is unable to solve the problem, report of such hazardous lights shall be forwarded to Director General, CAAN(Attention: Director, Department of Aerodrome Safety and Standards) within 3 working days of raising the report.
- 11.1.7 If asked by CAAN HQ to raise formal complaint against the owner / operator of the hazardous non-aeronautical light and / or LASER emitter in the local administration, the Aerodrome operator shall take immediate action on that, and shall follow up, as required.
- 11.1.8 Aerodrome operator shall keep Director (DASS) informed regularly.

11.2 Action by CAAN Headquarter

11.2.1 Director (DASS), personally or through a relevant Officer, engaged with the approval of Director General, make liaison with the owner / operator of the hazardous non-aeronautical light and / or LASER emitter and try to convince him to extinguish, shield or otherwise modify the light and / or LASER emitter, by explaining the probable fatal consequences of the hazardous lights.

March 2013 Rev. 0.00 Page xii

- 11.2.2 Will also try to make him understand that if the proposed corrective actions are not taken, CAAN will take the help of law enforcement agencies.
- 11.2.3 If the owner / operator does not take appropriate action, the CAAN may cause a notice to be served upon the owner of the place where the light is exhibited or upon the person having charge of the light directing the owner or person, within a reasonable time to be specified in the notice, to extinguish or to shield effectually the light in the manner specified in such notice.

In case the above actions fail, CAAN shall ask the Aerodrome operator to raise formal complaint in the local administration against the owner / operator of the hazardous non-aeronautical light and / or LASER emitter.

March 2013 Rev. 0.00 Page xiii